

Technical Notice

Replacement list for TL-battery types and terminations

Model TL-	Is replaced with model SL-	Degree of conformity	Size	Keyword (SL-model)
		FU = Same function, check with Application Engineering ID = technically identical NS = SL-model is not a standard product TD = TL-model discontinued		
TL-2100	SL-760	FU, TD	AA	Enhanced Start
TL-2134	SL-889	FU, TD	1/10 D	Extended Operating Life
TL-2135	SL-886	FU, TD	1/6 D	Extended Operating Life
TL-2150	SL-750	FU, TD	1/2 AA	Enhanced Start
TL-2155	SL-761	FU, TD	2/3 AA	Enhanced Start
TL-2186	SL-840	FU, TD	BEL	Extended Operating Life
TL-2200	SL-2770	FU, TD	C	Enhanced Start
TL-2300	SL-2780	FU, TD	D	Enhanced Start
TL-2450	---		Ø 24 x 6,5 mm	iXtra
TL-4902	SL-850	ID	1/2 AA	Extended Operating Life
TL-4903	SL-860	ID	AA	Extended Operating Life
TL-4920	SL-2870	ID	C	Extended Operating Life
TL-4930	SL-2880	ID	D	Extended Operating Life
TL-4934	SL-889	ID	1/10 D	Extended Operating Life
TL-4935	SL-886	ID	1/6 D	Extended Operating Life
TL-4955	SL-861	ID	2/3 AA	Extended Operating Life
TL-4986	SL-840	ID	BEL	Extended Operating Life
TL-5101	SL-350	FU, TD	1/2 AA	Standard Use and Stand-By
TL-5104	SL-360	FU, TD	AA	Standard Use and Stand-By
TL-5134	SL-889	FU, TD	1/10 D	Extended Operating Life
TL-5135	SL-886	FU, TD	1/6 D	Extended Operating Life
TL-5137	SL-2790	FU, TD	DD	Enhanced Start
TL-5151	SL-4350	FU, NS, TD	1/2 AA	Standard Use and Stand-By
TL-5155	SL-361	FU, TD	2/3 AA	Standard Use and Stand-By

Model TL-	Is replaced with model SL-	Degree of conformity	Size	Keyword (SL-model)
		FU = Same function, check with SOLi ID = technically identical NS = SL-model is not a standard product TD = TL-model discontinued		
TL-5186	SL-840	FU, TD	BEL	Extended Operating Life
TL-5242/W	SL-360/461	NS	(AA)	Battery Pack
TL-5276/W	---		(1/2 AA)	Battery Pack
TL-5293/W	SL-360/486	TD	(2x AA)	Battery Pack
TL-5315/F	---		(2x AA)	Battery Pack
TLL-5902	SL-750	ID	1/2 AA	iXtra
TL-5903	SL-760	ID	AA	iXtra
TL-5920	SL-2770	ID	C	iXtra
TL-5920/B	---		(C)	Battery Pack
TL-5930	SL-2780	ID	D	iXtra
TL-5930/F	---		(D)	Battery Pack
TL-5937	SL-2790	ID	DD	iXtra
TL-5955	SL-2761	ID	2/3 AA	iXtra
TL-5934	---		1/10 D	iXtra
TL-5935	---	TD	1/6 D	iXtra
TLH-2450	---		∅ 24 x 6,5 mm	Extended Temperature
TLH-5902	---		1/2 AA	Extended Temperature
TLH-5903	---		AA	Extended Temperature
TLH-5920	---		C	Extended Temperature
TLH-5930	---		D	Extended Temperature
TLH-5934	---		1/10 D	Extended Temperature
TLH-5935	---		1/6 D	Extended Temperature
TLH-5955	---		2/3 AA	Extended Temperature

Termination (TBL)	Termination (TBG)	Size	Designation
/S	/S		Standard
/P	/P	Ø 0,81 x 45 mm	Pins
/T	/T	3,17 x 7 mm	Tabs
/TP	/PTJ	7.5 mm	Polarized Tags double pins (-) 7.5 mm spacing
/PT	/PTPJ	7.5 mm	Polarized Tags double pins (+) 7.5 mm spacing
/PT2	/PR	0,7 x 5,5 mm	Pins Radial